

Model A2408, A2412-0, A2412-D

2.4 GHz Heavy Duty Omni-Directional Antennas



Model A2408

- 8 dBi gain
- Wide beamwidth
- Low profile



Model A2412-0

- 12 dBi gain
- No downtilt
- 5° beamwidth




Model A2412-D

- 12 dBi gain
- 3° downtilt
- 5° beamwidth



Mounting Details for Model A2412

Specifications

Model:	A2408	A2412-0	A2412-D
Frequency Range:	2400 - 2500 MHz	2400 - 2485 MHz	
Gain:	8 dBi	12 dBi	
Mounting Mast Diameter:	1" to 2.5"		
Impedance:	50 ohms		
VSWR:	< 2:1		
Radome:	Heavy-duty white UV inhibited fiberglass radome seal with internal copper elements		
Power Rating:	100 watts		
Vertical Beamwidth:	25°	5°	5° but with 3° downtilt
Termination:	N female connector		
Length:	16"	5'5"	
Weight:	2 lbs.	3 lbs. 8 oz.	
Wind Survival:	125 mph		
Wind Loading:	0.12 sq-feet	0.5 sq-feet	
Vertical Radiation Pattern:			
Ordering Information:	Model A2408 YDI P/N: 203-900009-001	Model A2412-0 203-900004-001	Model A2412-D 203-900003-001

All specifications subject to change without notice

Made in the U.S.A.

Rev A Apr 2004

8000 Lee Highway
Falls Church, VA 22042
Tel: (703) 205-0600 Fax: (703) 205-0610
Sales: 1-888-297-9090

www.ydi.com

990 Almanor Avenue
Sunnyvale, CA 94085
Tel: (408) 617-8150 Fax: (408) 617-8151
Sales: 1-800-664-7060